





^ %oCE • : Fluke 312 € • , f

| € • , f                 |            |             |
|-------------------------|------------|-------------|
| " ... † ... ± 50-500Hz) | ^ %o       | 40.00A      |
|                         |            | 400.0A      |
|                         |            | 1000A       |
|                         | Š < Œ      | 0.01A       |
|                         |            | 0.1A        |
|                         |            | 1A          |
|                         | • Ž •      | 1.9% ± 5•   |
|                         |            | 50-60Hz     |
|                         |            | 2.5% ± 5•   |
|                         | 60-500Hz   |             |
| " ... † • ± 50-500Hz)   | ^ %o       | 400.0V/750V |
|                         | Š < Œ      | 0.1V/1V     |
|                         | • Ž •      | 1.5% ± 5•   |
| ' ... † •               | ^ %o       | 400.0V      |
|                         |            | 1000V       |
|                         | Š < Œ      | 0.1V/1V     |
|                         | • Ž •      | 1% ± 2•     |
| † '                     | ^ %o       | 400.0       |
|                         |            | 4000        |
|                         | Š < Œ      | 0.1 /1      |
|                         | • Ž •      | 1% ± 3•     |
| " " ' •                 | " " ' •    | 10M         |
| — — — ~ TM              | — — — ~ TM | 500ms       |
| Š >                     | Š >        | 50          |
| œ • ž Ÿ                 | œ • ž Ÿ    | Ů2V         |
| i TM                    | i TM       | 1ms         |
| - **                    | Œ £ ¤ ¥ ** | 30→         |

, Ö

| S

36mm



