



TECHNICAL DATA

# Fluke 562/563 € • , f „ ... † ‡ ^ %



## Š < Œ •

Ä Å µ Æ

- 30:1/50:1 Ç È É Ê Ë , ¼ Ì Ç È † Š Í Î Ï Ð Ñ Ò
- Ó Ô 80PK-1 Õ Ç Ö × Ø Ù Ú Û Ü Ý
- Þ Æ È Æ à á 99â , ã ä å æ à á ç è
- † Š Ê Æ ' é USB Û è è ì
- í Ø Fluke View Basic ï ÿ , ð ñ ò ó Ê Æ ö ÷
- ø ù ú 0.1 ù 1.0 ù ý ¼ þ , ¼ † Š æ
- , € 1%
- 

## Ž • • ' : Fluke 562/563 € • , f „ ... † ‡ ^ %

... † ã ù ú ø ´ † ^ % ½ . ½¼ € ù ý þ ø ù ú ! Ê Æ à á " # \$ % & " ' ( ) ¶ • 3 \* + , - . / š 6 0 1 2 • ½ Fluke 562/563 € • , f „ ... † ‡ ^ % 3 × 4 • † Š 5 6 7 8 ) 9 " : ; ð ò \* < = \* + ½ 9 ¼ € ù ý þ ø ù ú ! Ê Æ à á " # \$ % & " Fluke 562/563 € • , f „ ... † ‡ ^ % > „ ? @ A „ • B Æ C D E ½¼ ð ñ F G H I • Ž J ç K ã ° L M N " O P Ž Q • Æ Ý R S ½ < „ T ¼ U Í V • F „ W X - Y Z Í € • Ž • [ ú "



Ž • ' " : Fluke 562/563 € • , f „ ... † ‡ ^ %

ƒ K \ Ê	F562	F563
^ , ] ^	-32_C ù 600_C	-32_C ù 760_C
'	$<0_C \alpha \backslash (1.0_C + 0.1_/1_C)$ $>0_C \alpha \backslash 1\% " \backslash 1.0_C \frac{1}{2} a b c$	
d x Æ	$\backslash e Ê \cdot 0.5\% "$ $\backslash 0.5_C \frac{1}{2} a f b$ c	
™ ^ g ú	0.1_C	
h i j F	8 ù 14 km	
j F l m (95%)	< 500 ms	
K n Õ ƒ Ö è o ^ , ] ^	-270_C ù 1372_C	
K n Õ ƒ Ö è o ,	è o , \ 2.2_C	$-270_C ù -40_C \alpha$ $\backslash (1_C + 0.2_C/1_C)$ $-40_C ù 1372_C \alpha$ $\backslash 1\% " 1_C \frac{1}{2} a f b c$
K n Õ ƒ Ö ^ g p	0.1_C	
Ç È ¨ h . q r š 90% Ý Š •	30:1	50:1

## Ordering information



### Fluke-562

Fluke 562 € • , f „ ...† ‡ ^ %

- Kn Ö Ç Ö
- 2 5s Ç t
- „ T u v

### Fluke-563

Fluke 563 € • , f „ ...† ‡ ^ %

- Kn Ö Ç Ö
- 2 5s Ç t
- „ T u v

### Optional accessories Description

3 „ Ç w x y 1,000 V • Fluke z { | } ~ 8 • Ð Linesman ~ €<sup>a</sup> • , ~ f „ ...† ” ’ é ‡ ^ • % Š < Ç • Ž ~ ê<sup>a</sup> 4. • „ • ’ ’ • „ ”

Ergonomic handles offer maximum torque and safety.

