

TECHNICAL DATA

Fluke 925€ • , f „ ...



† ‡ ^ %

- ĩ í • ' • ĩ ĩ ĐÑ
- òóƒõõö×Äø' • ƒ•
- ÄøÛúÛüƒŸ
- Þßà/Þáà' •
- â¿ãää...â
- 20. æçè—éêë.
- ì ï ±

Š < Œ • : Fluke 925€ • , f „ ...

Fluke 925î ¼ĩ Āđñð• €• , f„ ĀÄø ĩ í ó' • ƒ„ òƒ• ²ƒŸæððòƒ÷ð• øÛ™ƒ^ úûƒÖüƒ
 „ • ý' æ

Š < Ž • : Fluke 925€ • , f „ ...

€• , f

„ ...†

þÛ4ĩ ç9999Q=þÛ4ĩ ç9999Q=þÛ4ĩ ç9999Bú% àþÛ =ó' • ƒ„ ò.



± ^ %Š	f, -ft/m¢ ¯/· ¥ m/s¢ / ¥		
	f· -CMS¢m3/s¥¢ ĩ / ¥² CFM¢ft3/m¥¢ ĩ ¯/· ¥		
	fÝ - ²		
< ¢· Ž	ÜÜ		
•••	f, /f· ĩ - €· Å ò		
	fÝ ĩ - a >		
	Pá à/Pß à! "		
	# \$² %&Pá ² Pß		
' " " < • -	Ī ĺ ¢P' 2á (¥		
) â ĺ ¢Pâ 8* ¥		
— ~™Š	20· æ+, Ó- . /, ¢OÉ ò 1 2¥ÅØ34ª 2		
> ¢· Ž	0 5 50 ¢32 5 122 ¥.		
> ¢ÝŽ	P 6 80% 7 8 9:		
ı	9Vª ; ¢ 6 < • = >ª ; ¥		
¢ £ ¤	100 á (
¥ ^	363 g (0.8 lb)Å? Oª ; ² ĩ		
ı Š	@, - 181 x 71 x 38 mm (7.1 x 2.8 x 1.4 in)		
•••	A B 70 mm		
• ©ª	1i		
± ^ « <			
- - ± ^			
%Š	^ ®	- ° ±	² Ž
m/s¢ / ¥	0.40525.00 m/s	0.01 m/s	CD: • E 2%
ft/m¢ ¯/· ¥	8054900 ft/m	1 ft/m	CD: • E 2%
- ^ ± ^			
%Š	^ ®	- ° ±	² Ž
CMS¢ ĩ / ¥	0.01599.99m3/s	0.01	059.999m2
CFM¢ ĩ ¯/· ¥	159999ft3/m	1.0	059.999ft2
- •			
	^ ®	- ° ±	² Ž
	0 5 50 (32 5 122 ¥	0.1 /	E 0.8 (1.5)

Ordering information



Fluke 925

Fluke 925 € • , *f* „ ...

-
- 925*f* „
 - FGH
-

